

VOLA 5100, 5100X, 5200V, 5300
VOLA 5400DV, 5400V, 5400NV & A3/A4
VOLA 5400TV, 5400FV, 5400RV & A3/A4
VOLA 5600V & A3/A4

Fitting instruction
Montageanleitung
Monteringsvejledning



Monteringsvægledning
Montage hanleiding
Manuel de montage

www.vola.com

5000_V4_40998504
04-01-2023

5 705230 287317

vola.com	L	L1	L2	H	H1	D
5400DV	377 mm 14 3/4"	260 mm 10"	268 mm 10"	95 mm 3 3/4"	186mm 7 3/8"	70 mm 2 3/4"
5100, 5200V, 5300, 5400V, 5600V	475 mm 19 3/4"	355 mm 14"	367 mm 14 1/2"			
5100X, 5400NV, 5400TV	552 mm 21 3/4"	435 mm 17"	447 mm 17 5/8"			
5400FV, 5400RV	630 mm 25 1/2"	514 mm 20 3/8"	522 mm 20 1/2"			



A

Max.: 10 Bar/145 psi

Max. 65°C, 150°F

USA - For use with showerheads rated at 5.7 L/min. (1.5 gpm.) or higher.

Data, l/min. / (Gpm) 3 Bar/43.5 Psi:

5100/5200V/5300: 5400/5600A3: -

5400/5600: - 5400/5600A4: -

AUS - Hot water inlet: Max. 50°C, 122°F. (AS 4032)

5400 5600	5400A3 5600A3	5400A4 5600A4							
Out 2	Out 1	Out 1	32/(8.5)	16/(4.2)	-	-	-	-	-
Out 3	Out 2	Out 2	-	-	32/(8.5)	16/(4.2)	-	-	-
-	Out 3	Out 3	-	-	-	32/(8.5)	16/(4.2)	-	-
-	-	Out 4	-	-	-	-	-	16/(4.2)	32/(8.5)

B

Check the local legislation.
Bitte die örtlichen Vorschriften überprüfen.
Tjek de lokale regler.
Kontrollera lokala föreskrifter
Nazitten lokale regelgeving.
Vérifiez la législation locale.

!DO NOT!
!REMOVE!

C

DE:
Bitte separat beiliegende Anleitung für die Schallentkopplung VR972 beachten

D

Box till inbyggnadsblandare.
Boks til indbygningsblander.
Laatikko seinäasenteiselle sekoittajalle.

Ingår inte i leveransen, köps separat.
Ikke inkludert, kjøpes separat.
Eivät sisälly tilaukseen, ostettava erikseen.

200M

PEX1

Extension
Verlängerung
Forlængerdele
Förlängning
Aanpassing
Modification

T

Min. 3 mm
Max 65 mm

Y

Min. 48 mm
Max. 110 mm

	T	Y	VR5250/VR5410/VR2019
	3 - 15 mm	110 - 98 mm	Std.
	15 - 25 mm	98 - 88 mm	+10
	25 - 35 mm	88 - 78 mm	+20
	35 - 45 mm	78 - 68 mm	+30
	45 - 55 mm	68 - 58 mm	+40
	55 - 65 mm	58 - 48 mm	+50

Fitting of extension
Montage von verlängerung

Montering af forlængerdele
Montering av förlängning

VR5250

VR2019+, VR2119+

VR5410

5400:
5600:

5400A3/A4:
5600A3/A4:

VR5411

Extension, retrofit
Verlängerung, nachträglicher Einbau
Forlængerdele, eftermontering
Förlängning, eftermontering
Aanpassing na montage
Modification après installation

X

52 - 0 mm

X

-15 - 0 mm

	X	VR5250/VR5410/VR2019
	37 - 49 mm	Std.
	27 - 37 mm	+10
	17 - 27 mm	+20
	7 - 17 mm	+30
	-3 - 7 mm	+40
	-13 - -3 mm	+50

Montage van de verlengstukken
Montage des rallonges

5400/5600:


5400A3/ 5600A3:

5400A4:

5600A4:


1

vola



2x13 mm Lightweight wall
Leichtwand
Let væg


Lätta konstruktion
Holle wandconstructie
Construction légère



1x15 mm
1x18 mm
1x20 mm
2x13 mm


Lightweight wall
Leichtwand
Let væg

Lätta konstruktion
Holle wandconstructie
Construction légère



Masonry
Mauerwerk
Murværk

Murverk
Massieve wand
Mur Plein










2 Test Pressure
Prüfdruck
testtryk
Test tryck
Test druk
test de pression

Check the local legislation.
Bitte die örtlichen Vorschriften überprüfen.
Tjek de lokale regler.
Kontrollera lokala föreskrifter.
Nazitten lokale regelgeving.
Vérifiez la législation locale.


1. MAX. 16 Bar 232 Psi
2. MAX. 4 Bar 58 Psi

! Water - Wasser - Vand - Vatten - Water - L'eau
! MAX 1 Minute - Minut - Minuut !



Exploded view diagram of the VVA3 engine assembly. The diagram shows the following components and their assembly order:

- 5277LK**: Main engine block.
- 5268**: Piston and connecting rod assembly.
- 5410**: Piston pin.
- 5270 NV32**: Piston pin bush.
- 2C**: Piston pin clip.
- 5250**: Piston pin clip.
- 5249**: Piston pin clip.
- 5248**: Piston pin clip.
- 5246**: Piston pin clip.
- 5411**: Piston pin clip.
- 969**: Piston pin clip.
- 5269**: Piston pin clip.
- 972**: Piston pin clip (x8).
- 1902**: Piston pin clip.
- 968**: Piston pin clip.
- 2279/B/C**: Piston pin clip.
- 5273**: Piston pin clip.
- 5255**: Piston pin clip.
- 5262**: Piston pin clip.
- 5256**: Piston pin clip.
- Nr.52**: Piston pin clip.
- Nr.64**: Piston pin clip.
- 2A***: Piston pin clip.
- 3110**: Piston pin clip.
- 3109**: Piston pin clip.
- 2279**: Piston pin clip.
- 5277LK**: Main engine block.
- 5268**: Piston and connecting rod assembly.
- 5410**: Piston pin.
- 5270 NV32**: Piston pin bush.
- 2C**: Piston pin clip.
- 5250**: Piston pin clip.
- 5249**: Piston pin clip.
- 5248**: Piston pin clip.
- 5246**: Piston pin clip.
- 5411**: Piston pin clip.
- 969**: Piston pin clip.
- 5269**: Piston pin clip.
- 972**: Piston pin clip (x8).
- 1902**: Piston pin clip.
- 968**: Piston pin clip.
- 2279/B/C**: Piston pin clip.
- 5273**: Piston pin clip.
- 5255**: Piston pin clip.
- 5262**: Piston pin clip.
- 5256**: Piston pin clip.
- Nr.52**: Piston pin clip.
- Nr.64**: Piston pin clip.
- 2A***: Piston pin clip.
- 3110**: Piston pin clip.
- 3109**: Piston pin clip.
- 2279**: Piston pin clip.



©
2001

